

Product Data

No. 90 Dampproofing

3445 W. 31st. Place

Chicago, IL 60623

Phone: 773.247.7030

Fax: 773.247.7066

www.pureasphalt.comwww.suredrywaterproofing.com

DESCRIPTION

No. 90 Dampproofing is an asphalt cutback product designed for dampproofing below grade exterior of new commercial and residential foundations and concrete structures. No. 90 Dampproofing offers smoother, more consistent coverage, effectively sealing pores in concrete walls against infiltration of ground water. Spray application fills pores in the substrate, improving the bond with the foundation wall.

USES

As a dampproof coating, when sprayed without membrane on exterior of concrete and parged concrete block foundations to retard the passage of liquid water through walls below grade. Also protects concrete and masonry structures from liquids containing corrosive or disintegrating substances.

DRYING TIME

No. 90 Dampproofing is an asphalt cutback product designed for dampproofing below grade exterior of new commercial and residential foundations and concrete structures. No. 90 Dampproofing offers smoother, more consistent coverage, effectively sealing pores in concrete walls against infiltration of ground water. Spray application fills pores in the substrate, improving the bond with the foundation wall.

MEMBRANE PROPERTIES

Type:	Asphalt Cutback
Color:	Black
Density:	7.6 lbs/gal + or - .2
Application:	Airless spray, roller or brush

APPLICATION

No. 90 Dampproofing can be applied to surfaces at temperatures below freezing (down to 0°F).

SURFACE PREPARATION

All concrete and masonry to be coated must be clean and free of loose mortar, wires, fins or any other substance that might prevent bonding and placing of a continuous film.

PACKAGING/ STORAGE

Available in 55-gallon drums, 330-gallon totes, and 6,000-gallon tank wagons.

Contents are combustible. Keep away from excess heat, sparks, and sources of ignition. Store in a warm place for ease of use.

The information presented herein is based on the data available and is believed to be correct. However, nothing stated in this bulletin is to be taken as a warranty, expressed or implied regarding the accuracy of the information of the use of our product used singly or in conjunction with other products.