

Product Data

No. 66 Plastic Roof Cement Mastic

3445 W. 31st. Place

Chicago, IL 60623

Phone: 773.247.7030

Fax: 773.247.7066

www.pureasphalt.comwww.suredrywaterproofing.com

DESCRIPTION

Pure asphalt Plastic Roof Cement is a scientifically compounded composition of selected asphalts, mineral fibers and refined solvents that are manufactured to a heavy consistency for application by trowel to provide a durable, ductile coating of excellent adhesion and high resistance to water and weathering. When applied, this product dries to a tough, flexible, waterproof and corrosion proof coating that gives excellent performance over wide ranges of temperature and weather conditions. Pure Asphalt Plastic Roof Cement is available in three (3) consistencies: Summer, Spring-Fall, and Winter.

USES

Pure Asphalt Plastic Roof Cement is a general-purpose cement for repairing leaks in shingles, concrete, metal or asphalt roofs, flashings on walls, chimneys, flues, down-spouts and cornices. Excellent for sealing cracks in concrete, brick, as a joint filler for pre-cast roof slabs and general purpose use in maintenance of exposed buildings and structures.

ADVANTAGES

1. Easy to apply.
2. Excellent cure to properly applied film.
3. Tough, flexible, adhesive and cohesive film.
4. Excellent water and weather resistance.
5. Excellent adhesion.
6. Excellent lap cement.
7. Asbestos Free - eliminates liability.

PHYSICAL PROPERTIES

- Consistency: A smooth, heavy trowel consistency that will readily spread on and adhere to all surfaces without sagging.
- Character of dried film: Uniform, excellent adhesion to masonry, steel, slab insulation and other surfaces.
- The dried film retains its flexibility and ductility so that coating will resist extreme variations in temperature and weather.
- Has excellent resistance to flow at high temperature when used on a vertical surface.

APPLICATION

Spread Pure Asphalt Plastic Roof Cement to an average thickness of 1/8" (approximately 8 gallons per square) and press tightly into joints, seams or cracks. To repair large cracks, breaks and blisters, spread the Plastic Roof Cement over the damaged area, then embed cotton, glass or polymat membrane reinforcement, and then apply another coat of Plastic Roof Cement over the entire patch.

COVERAGE RATE

On porous or irregular surfaces, 3 gallons per 100 sq. ft. is recommended.

SURFACE PREPARATION

All surfaces should be clean, dry and free from oil or grease, dust, dirt, loose paint or other foreign matter.

SPECIFICATIONS

ASTM-D-4586 Type I

ASTM-D-3409

RED. SPEC. SS-C-153 Type I (Asbestos-Free)

PACKAGING

Available in 5-gallon pails and 55-gallon drums.

The information presented herein is based on the data available and is believed to be correct. However, nothing stated in this bulletin is to be taken as a warranty, expressed or implied regarding the accuracy of the information of the use of our product used singly or in conjunction with other products.