

Product Data

No. 89 Modified Bitumen Mastic

3455 W. 31st Place

Chicago, IL 60623

Phone: 773.247.7030

Fax: 773.247.7066

www.pureasphalt.comwww.suredrywaterproofing.com

DESCRIPTION

Pure Asphalt No. 89 Modified Bitumen Mastic is a HIGH STRENGTH, POLYMER MODIFIED ASPHALT MASTIC that provides excellent adhesion and excellent elongation properties. This is an asbestos-free formulation.

USES

Pure Asphalt No. 89 can be used to make repairs on existing modified applications and flashing on vertical surfaces, i.e. skylights, vents and pipes. No. 89 is recommended for use on new residential foundations to plug tie holes and repair irregularities.

ADVANTAGES

1. Easy to apply.
2. Excellent cure to properly applied film.
3. Tough, flexible, adhesive and cohesive film.
4. Excellent water and weather resistance.
5. Excellent adhesion.
6. Excellent lap cement.
7. Asbestos Free - eliminates liability.

PHYSICAL PROPERTIES

Weight per gallon	8.65 lbs
Shear Strength	26 lbs.
Peel Strength	13 lbs.
Elongation	250%
Recovery	95%
Cure Time	24 to 48 hrs
Flash Point	Above 103 F. /39.4 C. (Combustible)

APPLICATION

Apply Modified Bitumen at the rate of approximately 3 gallon per 100 square feet on horizontal surfaces and vertical surfaces. Irregular surfaces may require slightly more material per 100 sq. ft. Trowel or glove may be used to apply may be used to apply No. 89 Modified Bitumen Mastic.

COVERAGE RATE

On porous or irregular surfaces, 3 gallons per 100 sq. ft. is recommended.

SURFACE PREPARATION

All surfaces should be free from oil, grease, dirt and loose materials. All surfaces should be patched and repaired with mastic.

SPECIFICATIONS

ASTM-D-3019 TYPE III

ASTM-D-3409

PACKAGING

Available in 5-gallon pails and 55-gallon drums.

The information presented herein is based on the data available and is believed to be correct. However, nothing stated in this bulletin is to be taken as a warranty, expressed or implied regarding the accuracy of the information of the use of our product used singly or in conjunction with other products.